



JUST BUILDTech & CO.

Manufacturer of tile adhesives & Precast U Drain & Wall

📍 Village: Karan, Palsana, Surat ☎ 080082 61262 ✉ jitendra.buildtech@gmail.com | sale.buildtech@gmail.com

SURAT | RAIPUR | HYDERABAD



JUST BUILDTech & CO.

Manufacturer of tile adhesives &
Precast U Drain & Wall

Jitendra Patel
☎ 080082 61262





JUST BUILDTech & CO.

About Us

Just Buildtech & Co. is considered as one of the leading supplier of construction chemical products in India. Just Buildtech & Co. is faster growing Indian company in the field of construction chemical. Our product range of construction chemicals such as tile adhesives, mortar & ready mix plaster.

Company Strategy

Our world is nothing more than the extension of our personality. A signature that is individual and unique an irreplaceable stamp of our soul.

Our choice leads us and our taste defines us.

Purpose to be a leader in constructions chemical industry by providing enhanced product, service, relationship and profitability.

OUR PRODUCTS




ADHESIVE



Light U Drain



Havey U Drain



Box Culvert



Singal Wall Panel

SILVER

A balance in
style and durability.

TYPE 2

SILVER ADHESIVE

Tile Fixing adhesive for internal wall & floor applications.



Product Details

Silver Tilefix Adhesive is a cement- based, polymer modified, high quality tile adhesive recommended for fixing vitrified tiles on floors & walls in internal areas.

Pack	20 Kg 40 Kg
Coverage (As Per 20kg)	60 sq.ft. @ 3mm (as per lab conditions)
Color	Grey
Shelf Life	12 Month



Technical Specification (Complies To IS 15477-2019)

Water Powder Ratio	25 ± 2%
Pot Life	1 hour 30 minutes ± 15 minutes
Open Time	25 - 30 Minutes
Adjustment time	25 - 30 Minutes
Usag Time Post Application	24 Hours
Compressive Strength @28 Days (N/mm ²)	10-11 N/mm ²
Tensile Adhesion Strength @ 28 Days	1.90 N/mm ²
Shear Adhesion Strength @ 28 Days	2.02 N/mm ²

Areas of Application

Silver Tile Adhesive is ideal for internal thin bed wall and floor applications of vitrified tiles. It is recommended to be used over cementitious substrates and for tile - on tile applications.

Features & Benefits

- Excellent adhesion to substrate
- Enhances durability
- High slip resistance
- Self-curing
- Extended open time allowing more time for tile fixing
- Single component : easy-to-use
- Pre-soaking of tiles isn't required

GOLD

A balance in style and durability.

TYPE 3

GOLD ADHESIVE

Tile Fixing adhesive for Internal / External wall & floor applications.



Product Details

Gold Tilefix is a cement-based, polymer modified, high quality tile adhesive recommended for fixing tiles and natural stones on floors & walls in internal areas, and can also be used for external wall & floor applications.

Pack	20 Kg 40 Kg
Coverage (As Per 20kg)	60 sq.ft. @ 3mm (as per lab conditions)
Color	Grey
Shelf Life	12 Month



Technical Specification (Complies To IS 15477-2019)

Water Powder Ratio	25 ± 2%
Pot Life	2 hour ± 15 minutes
Open Time	25 - 30 Minutes
Adjustment time	25 - 30 Minutes
Usage Time Post Application	24 Hours
Compressive Strength @28 Days (N/mm ²)	16-17 N/mm ²
Tensile Adhesion Strength @ 28 Days	2.09 N/mm ²
Shear Adhesion Strength @ 28 Days	2.50 N/mm ²

Area of Application

Gold Tilefix is ideal for internal thin bed wall & floor and external floor & wall applications of tiles, natural stones, granite & marble. It is recommended to be used over cementitious substrates and for tile-on tile applications.

Features & Benefits

- Excellent adhesion to substrate
- Enhances durability
- Self-curing
- Pre-soaking of tiles isn't required
- Single component : easy to use
- High slip resistance
- Extended open time allowing more time for tile fixing

PLATINIUM

A balance in style and durability.

TYPE 4

PLATINIUM ADHESIVE

Tile Fixing adhesive for Internal / External wall & floor applications.



Product Details

Platinum Tilefix is a cement - based, polymer modified, high quality and high strength tile adhesive recommended for fixing large format tiles, natural stones thin tiles on floors and walls in internal and external areas.

Pack	20 Kg
Coverage	60 sq.ft. @ 3mm (as per lab conditions)
Color	Grey
Shelf Life	12 Month



Technical Specification (Compiles To IS 15477-2019)

Water Powder Ratio	25 ± 2%
Pot Life	2 hour 30 minutes ± 15 minutes
Open Time	25 - 30 Minutes
Adjustment time	25 - 30 Minutes
Usag Time Post Application	24 Hours
Compressive Strength @28 Days (N/mm ²)	21-22 N/mm ²
Tensile Adhesion Strength @ 28 Days	2.48 N/mm ²
Shear Adhesion Strength @ 28 Days	2.89 N/mm ²

Area of Application

Platinum Tilefix is ideal for both internal & external, thin bed wall & floor applications. It is recommended for fixing large format natural stones, tiles and for tile-on-tile applications of large format vitrified tiles. It is also applications of tiles/stones over dry walls.

Features & Benefits

- Excellent adhesion to substrate
- Self-curing
- Single component : easy to use
- Enhances durability
- Suitable for varied substrates
- Flexible adhesive which can withstand low to medium vibrations
- High slip resistance
- Extended open time allowing more time for tile fixing

JB JOINTS

A balance in style and durability.



Product Details

JB JOINTS - is a thin jointing mortar for AAC blocks masonry work. It is specially designed to provide high strength and durable bonding between the blocks.

Pack	40 Kg
Coverage	3-5 sq.ft. for block thickness of 100mm
Color	Grey
Shelf Life	12 Month

JB JOINTS - Block Jointing Mortar



Technical Data Sheet

Water Powder Ratio	25 ± 2%
Pot Life	1 hour 30 minutes ± 15 minutes
Usag Time Post Application	24 Minutes
Compressive Strength @28 Days (N/mm ²)	9-10 N/mm ²
Tensile Adhesion Strength @ 28 Days	1.25 N/mm ²

Area of Application

JB JOINTS is recommended to be used for masonry wall preparation for joining all types of autoclaved aerated concrete blocks and fly ash bricks.

Features & Benefits

- Economical - Save substantial cost compared to conventional mortar
- No Shrinkage cracks at joints
- High tensile adhesion strength at joints
- Self-curing
- Thin bed joints
- Ready for subsequent application in 24 hours
- Saves time - Eliminates lengthy and cumbersome process of site mixing
- Uniform and consistent quality

JB PLAST

A balance in
style and durability.



Product Details

JB PLAST - is a cement based, plastering mortar for application over masonry walls, RCC columns, beams and ceiling areas. It provides a strong surface suitable for all types of final finishing applications.

Pack	40 Kg
Coverage	18-20 sq.ft. @ 12mm (Depending on the substrate)
Color	Grey
Shelf Life	12 Month

JB PLAST - Ready Mix Plaster



Technical Data Sheet

Water Powder Ratio	17-19 %
Pot Life	1 Hour
Compressive Strength @28 Days (N/mm ²)	9-10 Mpa
Thickness of layer	8-15 mm per coat
Water Curing	2-3 Times for 2-3 days
Wastage	Negligible
Final Finish	Excellent

Area of Application

JB PLAST is ideal for plastering on inner and outer walls. IT is recommended to be used effectively on brick, block stone walls as well as concrete surfaces. Highly recommended for well-prepared walls requiring thickness of plaster up to 15mm in a single layer.

Features & Benefits

- Excellent replacement to conventional plaster
- Well graded sand & additives ensure consistent quality
- Needs lesser curing than conventional plaster
- Provides uniform and smooth finish to walls
- Lesser rebound loss than conventional plaster
- Speedy work due to convenience in application
- Minimal wastage